SHRINKING TUBES

intercable

Minibox 2:1 black, Type: W 135B

Material: polyolefin, black color, shrinking ratio 2:1
thin-walled
flame-protected (low smoke at burning)

Size (inches)	Inner Ø (mm)		Art. N.	Wall thickness (mm) after shrinking	M in box
	before shrinking	after shrinking			
3/64	1,2	0,6	**ICC65047**	0,41	15
1/16	1,6	0,8	**ICC65050**	0,43	15
3/32	2,4	1,2	**ICC65053**	0,51	15
1/8	3,2	1,6	**ICC65056**	0,51	15
3/16	4,8	2,4	**ICC65059**	0,51	10
1/4	6,4	3,2	**ICC65062**	0,64	10
3/8	9,5	4,8	**ICC65065**	0,64	10
1/2	12,7	6,4	**ICC65068**	0,64	5
3/4	19,1	9,6	**ICC65071**	0,77	5
1	25,4	12,7	**ICC65074**	0,89	5

Minibox 2:1 green/yellow, Type: W 135B gr/ye

Material: polyolefin, green/yellow color, shrinking ratio 2:1
thin-walled
flame-protected (low smoke at burning)

Size (inches)	Inner Ø (mm)		Art. N.	Wall thickness (mm) after shrinking	M in box
	before shrinking	after shrinking			
3/64	1,2	0,6	**ICC65447**	0,41	15
1/16	1,6	0,8	**ICC65450**	0,43	15
3/32	2,4	1,2	**ICC65453**	0,51	15
1/8	3,2	1,6	**ICC65456**	0,51	15
3/16	4,8	2,4	**ICC65459**	0,51	10
1/4	6,4	3,2	**ICC65462**	0,64	10
3/8	9,5	4,8	**ICC65465**	0,64	10
1/2	12,7	6,4	**ICC65468**	0,64	5
3/4	19,1	9,6	**ICC65471**	0,77	5
1	25,4	12,7	**ICC65474**	0,89	5

2:1 black, Type: W 135B

E 355596

Material: polyolefin, black color, shrinking ratio 2:1
thin-walled
flame-protected (low smoke at burning)

Size (inches)	Inner Ø (mm)		Art. N.	Wall thickness (mm) after shrinking	Packing unit m / reel
	before shrinking	after shrinking			
1/16	1,6	0,8	**ICC65001**	0,4	150
3/32	2,4	1,2	**ICC65003**	0,5	150
1/8	3,2	1,6	**ICC65006**	0,5	150
3/16	4,8	2,4	**ICC65009**	0,5	75
1/4	6,4	3,2	**ICC65012**	0,6	75
3/8	9,5	4,8	**ICC65015**	0,6	75
1/2	12,7	6,4	**ICC65018**	0,6	50
3/4	19	9,5	**ICC65021**	0,8	30
1	25,4	12,7	**ICC65024**	0,9	30
1¼	31,8	15,9	**ICC65027**	0,9	30
1½	38	19	**ICC65030**	1,0	30

2:1 transparent, Type: W 135 tr

Material: polyolefin, transparent, shrinking ratio 2:1
thin-walled

Size (inches)	Inner Ø (mm)		Art. N.	Wall thickness (mm) after shrinking	Packing unit m / reel
	before shrinking	after shrinking			
1/16	1,6	0,8	**ICC65701**	0,4	150
3/32	2,4	1,2	**ICC65703**	0,5	150
1/8	3,2	1,6	**ICC65706**	0,5	150
3/16	4,8	2,4	**ICC65709**	0,5	75
1/4	6,4	3,2	**ICC65712**	0,6	75
3/8	9,5	4,8	**ICC65715**	0,6	75
1/2	12,7	6,4	**ICC65718**	0,6	50
3/4	19	9,5	**ICC65721**	0,8	30
1	25,4	12,7	**ICC65724**	0,9	30
1¼	31,8	15,9	**ICC65727**	0,9	30
1½	38	19	**ICC65730**	1	30

3:1 black, Type: W 135

Material: polyolefin, black color, shrinking ratio 3:1
thin-walled
flame-protected (low smoke at burning)

Size (inches)	Inner Ø (mm)		Art. N.	Wall thickness (mm) after shrinking	Packing unit m / reel
	before shrinking	after shrinking			
1/8	3,2	1	ICC65106	0,55	150
1/4	6,4	2	ICC65112	0,65	75
3/8	9,5	3	ICC65115	0,75	75
1/2	12,7	4	ICC65118	0,75	50
3/4	19	6	ICC65121	0,85	30
1	25,4	8	ICC65124	1	30
1½	39	13	ICC65130	1,15	30

3:1 black, Type: WKS

Material: polyolefin, black color, shrinking ratio 3:1
thin-walled
flame-protected (only outside layer), with adhesive

Inner Ø (mm)		Art. N.	Wall thickness (mm) after shrinking	carton / pcs pcs x 1,22 m
before shrinking	after shrinking			
6	2	**ICC65212**	1,2	1/10
9	3	**ICC65215**	1,4	1/10
12	4	**ICC65218**	1,7	1/10
19	6	**ICC65221**	2,1	1/10
24	8	**ICC65224**	2,4	1/10
40	13	**ICC65227**	2,4	1/10

3:1 black, Type: WDW

Material: polyolefin, black color, shrinking ratio 3:1
thick-walled
not flame-protected, with adhesive

Inner Ø (mm)		Art. N.	Wall thickness (mm) after shrinking	carton / pcs pcs x 1,22 m
before shrinking	after shrinking			
13	4,1	**ICC65318**	2,4	1/75
19,1	6,1	**ICC65321**	2,4	1/75
27,9	8,9	**ICC65324**	3	1/75
38,1	11,9	**ICC65325**	4,1	1/40
50,8	16	**ICC65327**	4,1	1/25
68,1	22,1	**ICC65330**	4,1	1/15
89,9	30	**ICC65333***	4,1	1/10
119,9	39,9	**ICC65336***	4,3	1/5

3:1 green/yellow, Type: W 135

Material: polyolefin, green/yellow color, shrinking ratio 3:1
thin-walled
flame-protected (low smoke at burning)

Size (inches)	Inner Ø (mm)		Art. N.	Wall thickness (mm) after shrinking	carton / pcs pcs x 1,22 m
	before shrinking	after shrinking			
1/8	3,2	1	**ICC65406**	0,55	1/25
1/4	6,4	2	**ICC65412**	0,65	1/10
3/8	9,5	3	**ICC65415**	0,75	1/10
1/2	12,7	4	**ICC65418**	0,75	1/10
3/4	19	6	**ICC65421**	0,85	1/10
1	25,4	8	**ICC65424**	1	1/10

3:1 blue, Type: W 135

Material: polyolefin, blue color, shrinking ratio 3:1
thin-walled
flame-protected (low smoke at burning)

Size (inches)	Inner Ø (mm)		Art. N.	Wall thickness (mm) after shrinking	carton / pcs pcs x 1,22 m
	before shrinking	after shrinking			
1/8	3,2	1	**ICC65506**	0,55	1/25
1/4	6,4	2	**ICC65512**	0,65	1/10
3/8	9,5	3	**ICC65515**	0,75	1/10
1/2	12,7	4	**ICC65518**	0,75	1/10
3/4	19	6	**ICC65521**	0,85	1/10
1	25,4	8	**ICC65524**	1	1/10

2:1 black, Type: WHF

DEF STAN 59/97

Material: polyolefin, black color, shrinking ratio 2:1
flame-protected (low smoke at burning)

Size (inches)	Inner Ø (mm)		Art. N.	Wall thickness (mm) after shrinking	Packing unit m / reel
	before shrinking	after shrinking			
1/8	3,2	1,6	**ICC65606**	0,51	300
3/16	4,8	2,4	**ICC65609**	0,51	300
1/4	6,4	3,2	**ICC65612**	0,64	300
3/8	9,5	4,8	**ICC65615**	0,64	150
1/2	12,7	6,4	**ICC65618**	0,64	100
3/4	19	9,5	**ICC65621**	0,76	50
1	25,4	12,7	**ICC65624**	0,89	50
1½	38	19	**ICC65630**	1,02	50

Selection Box

Assortment box made of high quality plastic, filled with colored shrink tubing sections of sizes 1.2 / 0.6 mm - 12.7 / 6.4 mm in the colors black, red, yellow, blue and white.
For exact content see following table.

Continuous operating temperature: -55 ° C to + 125 ° C
Minimum shrinking temperature: + 110 ° C

Nr.	Size (inches)	Inner Ø (mm)		Wall thickness (mm) after shrinking	Long mm	Pcs	Color
		before shrinking	after shrinking				
1	3/64	1,2	0,6	0,4	40	each 25	black, yellow, white, red, blue
2	1/16	1,6	0,8	0,4	40	each 25	black, yellow, white, red, blue
3	3/32	2,4	1,2	0,5	40	each 25	black, yellow, white, red, blue
4	1/8	3,2	1,6	0,5	40	each 20	black, yellow, red, blue
5	3/16	4,8	2,4	0,5	40	each 10	black, yellow, red, blue
6	1/4	6,4	3,2	0,6	40	each 5	black, yellow, red, blue
7	3/64	1,2	0,6	0,4	250	5	blue
	1/16	1,6	0,8	0,4	250	5	red
	1/8	3,2	1,6	0,5	250	5	blue
	3/16	4,8	2,4	0,5	250	5	yellow
	1/4	6,4	3,2	0,6	250	5	black
	3/8	9,5	4,8	0,6	250	3	black
8	3/8	9,5	4,8	0,6	125	each 4	yellow, red, blue
9	1/2	12,7	6,4	0,6	125	each 3	yellow, red, blue
						Art. N.:	**ICC90859**